

ECT: St. Joseph Cemetery - Avon
Neil Jereb - Lighting and Controls, Inc.
:: 2/14/17

re height = 42"
plane = 0' (ground)
points @ 5' x 5'

Statistics					
Description	Symbol	Avg	Max	Min	Max/Min Avg/Min
Drive	+	0.3 fc	5.5 fc	0.0 fc	N/A N/A

Schedule				Description			
Symbol	Label	Quantity	Manufacturer	Catalog Number			
⤴ ⦿	A	10	EATON - INVUE (FORMER COOPER LIGHTING)	ABB-B2-LED-D1-A	ARBOR OUTDOOR ARCHITECTURAL BOLLARD 70 CRI, 4000K LEDs AND ASYMMETRIC OPTIC, GRAPHITE METALLIC PAINTED FINISH ABSOLUTE PHOTOMETRY IS BASED ON CALIBRATION FACTORS CREATED USING LAB LUMEN STANDARDS IN GONIOPHOTOMETER WITH TEST DISTANCE OF 28.75 FEET Street, Underpass, Walkway, Direct, Emergency, Corrosion Resistant, Damp Location, Hose Down, Retrofit, Vandal Resistant, Waterproof, Wet Location		
					Number Lamps	Lumens Per Lamp	Light Loss Factor
					1	848	0.9
							23

